

# HIX IMPRINT

## Flash Cure Units

HIX® meets your flash cure needs at every stage of your business. From the easy to use, price conscious, manual VS-1818 model to the Premier® 1818 model with advanced features like an auto cycling heat head to prevent garment scorching, HIX has the perfect solution.

At the heart of every HIX flash cure unit is a high performance and efficient Infra-Red heating element that is factory built in the USA. The HIX exclusive accu-therm thermocouple design found on all Premier Series units has set the industry standard for precise temperature control.

For even greater energy savings look at the HIX® Premier® flash cure model. The Premier 1818 is equipped with heat sink technology to reduce energy consumption by more than 70%. The heat sink minimizes the heater cycling resulting in lower energy bills and longer heater life. It's also equipped with a manual cycle foot control switch that speeds up production for faster job turn around and bigger profits



## Flash Cure Units

### Overview

- Constructed around the same Infra-red heating elements as our Premier® dryer series; all elements are made in the USA, are model-specific, and carry a 3-year first-owner warranty.
- Adjustable height allows control of the distance between the garment and the heater panel.
- Digital controller for temperature and up to four user presets.
- Pairs well with the HIX® Premier® manual screenprinter floor models

### Premier® SH-1818 Design

- Uses a heat sink, saving energy by retracting the heat head over a ceramic heat-sink while in standby mode. This traps the heat, resulting in electricity savings of around 70%.
- Manual/auto settings for the automatic retraction of the arm to the heat sink with or without using the foot switch.

# FEATURES

- All Metal Construction
- Adjustable height from 28" to 48"
- Lifetime warranty on the frame
- 1 year warranty on all electronics

## CERTIFICATIONS

- CE
- ETL Certified to UL & CSA Standards



### MSH-1818E

### SH-1818

#### DIMENSIONS (W,H,D)

**Width:** 32 inches  
**Height:** Adjustable 28-48 inches  
**Depth:** 21 inches  
**Weight:** Unit only 71 lbs

#### DIMENSIONS (W,H,D)

**Width:** 32 inches  
**Height:** Adjustable 28-48 inches  
**Depth:** 21 inches  
**Weight:** Unit only 119 lbs

#### SHIPPING DIMENSIONS

**Shipping Width:** 48 inches  
**Shipping Height:** 18 inches  
**Shipping Depth:** 48 inches  
**Shipping Weight:** 101 lbs\*

#### SHIPPING DIMENSIONS

**Shipping Width:** 26 inches  
**Shipping Height:** 23 inches  
**Shipping Depth:** 42 inches  
**Shipping Weight:** 149 lbs\*

#### ELECTRICAL

120 Volt / 60 Hz  
1631 Watts  
13.6 Amps

220 Volt / 60 Hz  
1631 Watts  
7.3 Amps

#### ELECTRICAL

120 Volt / 60 Hz  
2200 Watts  
18.5 Amps

220 Volt / 60 Hz  
2200 Watts  
9.5 Amps

\* Single machine will ship freight on a pallet. Request lift-gate or indicate residential shipping if necessary.  
HIX® Corporation recommends all equipment is installed with surge protection & in a climate controlled environment for best results.



*HIX® Corporation Graphics Division*  
Product improvement may require  
specifications to change without notice

hixcorp.com  
800-835-0606  
1201 E. 27th Terrace  
Pittsburg, KS 66762  
USA

All specifications are subject to change without notice.

HIX® Corporation recommends all equipment is installed with surge protection & in a climate controlled environment for best results.

