

Specialty Heat Transfer Machine

B-250

BALL CAP

The HIX® B-250 is a portable cap press that's durable enough for hi-volume production but lightweight enough to take to a show. They feature the same lifetime warranty on the heat casting, full color LCD touchscreen controller, and high performance rubber pads that we use on our other presses and the supplied transfer hold down blanket ensures your transfer won't shift during production.



FH-3000

FLAT | CUBE

The HIX® FH-3000 press gives you the ability to apply transfers to shirt pockets, sleeves, cuffs, collars, bags, aprons, name badges, tiles, gloves, and other small applications. What makes this press stand out is its ability to give great control on small items, odd shapes, and unwieldy products. The FH-300 comes with the flat attachment and the cube attachment can be purchased as an option.



B-250 FH-3000

Overview

These presses are a manual machine which features a features a digital timer that is adjustable up to 99 minutes and 59 seconds, shows countdown on readout, beeps after elapsed time, and resets when the open and close handle is raised. With full range pressure adjustment to work with every project.

B-250 Design

- The innovative bottom cap hold-down stretches the cap out, holding it snug to the lower (rubber covered) platen.
- A Teflon blanket is suspended between the upper and lower platen to hold the transfer (or lettering) in place before the heating element is locked down.

FH-3000 Design

- The flat attachement will do a maximum area of 3-3/4"x6".
- The flat and cube attachments are easily interchangeable.
- The cube attachment can be used for cube photo displays or any square up to 3-1/2".

FEATURES

- · All Metal Construction
- Integrated full color LCD touchscreen controller
- Up to four programmable presets
- Available as 120v or 220v
- Lifetime warranty on heating element

B-250 Features

- Includes three interchangeable lower platen sizes
- PTFE hold down blanket keeps transfers in place
- Spring loaded cap hold down keeps tension on the cap to the lower platen

FH-3000 Features

- Interchangeable lower platens (flat or cube)
- Ideal for small transfer surfaces

TEMPERATURE RANGE

Off - 450°F (232°C) upper platen

CERTIFICATIONS

 ETL Certified to UL & CSA Standards

ACCESSORIES (Not Included)

- PTFE Trasfer Sheet (4" x 12")
- B-250 Cap Bracket & PTFE Blanket
- B-250 Replacement PTFE Blanket
- FH-3000 Cube Attachment (3.5" x 3.5")
- · Replacement Pad Kits







DIMENSIONS (W,H,D)

Width: 12 inches

Height: 21 inches (handle up)

Depth: 16 inches

Weight: Press only 25 lbs

SHIPPING DIMENSIONS

Shipping Width: 19 inches Shipping Height: 16 inches Shipping Depth: 19 inches Shipping Weight: 35 lbs

ELECTRICAL

120 Volt / 60 Hz 450 Watts 4 Amps

220 Volt / 60 Hz 430 Watts 2 Amps



DIMENSIONS (W,H,D)

Width: 16 inches Height: 19 inches Depth: 19 inches

Weight: Press only 20 lbs

SHIPPING DIMENSIONS

Shipping Width: 19 inches Shipping Height: 16 inches Shipping Depth: 19 inches Shipping Weight: 30 lbs

ELECTRICAL

120 Volt / 60 Hz 450 Watts 4 Amps

220 Volt / 60 Hz 430 Watts 2 Amps

HIX® Corporation recommends all equipment is installed with surge protection & in a climate controlled environment for best results.



HIX® Corporation Graphics Division
Product improvement may require
specifications to change without notice

hixcorp.com

800-835-0606

1201 E. 27th Terrace Pittsburg, KS 66762 USA



